



SIMATIC DP, Electronics module for ET 200S, 1 SSI 25 bit/1 MHz 15 mm width, Module for connection of absolute value encoders with SSI Synchronous Serial Interface with DI and comparison value with clock synchronization

Supply voltage

Load voltage L+

• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
• Reverse polarity protection	Yes

Input current

from load voltage L+ (without load), max.	40 mA
from backplane bus 3.3 V DC, max.	10 mA

Encoder supply

24 V encoder supply

• 24 V	Yes
• Short-circuit protection	Yes
• Output current, max.	500 mA

Absolute encoder (SSI) encoder supply

• Absolute encoder (SSI)	Yes
• Type of output voltage	L+ (-0.8 V)
• Short-circuit protection	Yes
• Output current, max.	500 mA

Power loss

Power loss, typ.	1 W
------------------	-----

Hardware configuration

Module exchange

• Module exchange during operation of the IM-DP	Yes
• Module exchange under process voltage	Yes

Digital inputs

Number of digital inputs	1
--------------------------	---

Input voltage

• for signal "0"	-30 to +5 V
• for signal "1"	+11 to +30V

Input current

• for signal "0", max. (permissible quiescent current)	2 mA
• for signal "1", typ.	9 mA

Input delay (for rated value of input voltage)

for standard inputs

— at "0" to "1", max.	300 µs
— at "1" to "0", max.	300 µs

Cable length

• shielded, max.	50 m
------------------	------

Encoder	
Number of connectable encoders, max.	1
Connectable encoders	
• Absolute encoder (SSI)	Yes
• 2-wire sensor	Yes; Type 2
Encoder signals, absolute encoder (SSI)	
• Input signal	to RS-422
• Telegram length, parameterizable	13, 14, 16, 21, 24 & 25 bit
• Binary code	Yes
• Gray code	Yes
• Cable length, shielded, max.	320 m; At 125 kHz
• Monoflop time	16/32/48/64 µs
Interrupts/diagnostics/status information	
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital input (green)	Yes
• Status indicator forward counting (green)	Yes
• Status indicator backward counting (green)	Yes
Potential separation	
Potential separation digital inputs	
• Potential separation digital inputs	No; same potential with L+ and SSI
Potential separation counter	
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	No
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	40 g

last modified: 1/16/2021 