



Figure similar

### MLFB-Ordering data

6SL3210-5HE11-0UF0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		Communication	
<b>Input</b>		Communication	PROFINET
Number of phases	3 AC	<b>Ambient conditions</b>	
Line voltage	200 ... 480 V ±10 %	Installation altitude	1000 m (3280.84 ft)
Line frequency	45 ... 66 Hz	Cooling	Air cooling using an integrated fan
Rated current	3.8 A	<b>Ambient temperature during</b>	
Inrush current	4.3 A	Operation	0 ... 50 °C (32 ... 122 °F) Better than class 3K3, in acc. with EN 60721-3-3: 2002, without derating
<b>Output</b>		Transport	-40 ... 70 °C (-40 ... 158 °F) Class 2K4, in acc. with EN 60721-3-2: 1997, in transport packaging
Number of phases	3 AC	Storage	-25 ... 55 °C (-13 ... 131 °F) Class 1K4, in acc. with EN 60721-3-1: 1997, in product packaging
Rated power (at 400V)	1.00 kW ( 1.36 hp )	<b>Relative humidity during</b>	
Rated current I <sub>N</sub>	3.0 A	Max. operation	95 % RH, condensation not permitted
Max. output current	10.9 A	Transport, max.	95 % at 40 °C (104 °F)
Pulse frequency	8 kHz	Bearing, max.	95 %
Output frequency for servo control	0 ... 550 Hz		
<b>Electronics power supply</b>			
Voltage	24 V -15 % ... +20 %		
Current demand, max.	1.0 A		



Figure similar

Inputs / outputs		Connections	
<b>Standard digital inputs</b>		<b>Line side</b>	
Number	5 of which 2 for F-DI	Version	push-in spring-type terminals
		Conductor cross-section	0.75 ... 6.00 mm <sup>2</sup> / 18 ... 10 AWG
<b>Fail-safe digital inputs</b>		<b>Motor end</b>	
Number	1 Can only be used for STO/SS1	Version	push-in spring-type terminals
		Conductor cross-section	0.75 ... 6.00 mm <sup>2</sup> / 18 ... 10 AWG
<b>Mechanical data</b>		<b>DC link (for braking resistor)</b>	
<b>Dimensions</b>		Version	push-in spring-type terminals
Width	50.0 mm (1.97 in)	Conductor cross-section	0.75 ... 6.00 mm <sup>2</sup> / 18 ... 10 AWG
Height without shield plate	273.0 mm (10.75 in)	Cable length	10 m (32.81 ft)
Depth	223.0 mm (8.78 in)	<b>PE connection</b>	
Mounting position	vertical wall mounting	Version	M4 screw studs
Degree of protection	IP20 / UL open type	<b>Max. motor cable length</b>	
Frame size	FSA	Shielded	50 m (164.04 ft)
Net weight	2.10 kg (4.63 lb)	<b>Standards</b>	
		Compliance with standards	CE, cULus, RCM, KC, EAC
		CE marking	Low-voltage directive 2006/95/EC
		Verification of suitability for fail-safety	SIL 2 in acc. with IEC 61508 parts 1-3 (2010) and IEC 61800-5-2 (2016), PL d in acc. with ISO 13849 part 1 (2015), Category 3 in acc. with IEC 60204 (2007)