

# Product datasheet

Specifications



## voltage transformer - 230..400 V - 1 x 230 V - 1600 VA

ABL6TS160U

! Discontinued on: 22 July 2020

ABL6TS160U has not been replaced. Please contact your customer care centre for more information.

! Discontinued

### Main

Range of product	Modicon Transformer Optimized
Product or component type	Safety and isolation transformer
Rated power in VA	1600 VA
Input voltage	230 V AC single phase, terminal(s): N-L1 400 V AC phase to phase, terminal(s): L1-L2
Output voltage	230 V AC
Secondary winding	Single
Protective cover	Without
Ambient air temperature for operation	-20...50 °C

### Complementary

Input voltage limits	360...440 V 207...253 V
Network frequency limits	47...63 Hz
Input voltage tolerance	+/- 15 V
Efficiency	96 %
Power dissipation in W	66.7 W
Output sustained overvoltage	3 % (no load, hot state)
Maximum voltage drop at rated load	0 %
No load losses	23.7 W
Short-circuit voltage	0,0265
Output protection type	Against overload, protection technology: external Against overvoltage, protection technology: external Against short-circuits, protection technology: external
Connections - terminals	For input connection: screw type terminals, connection capacity: 5 x 4 mm <sup>2</sup> AWG 11 For input ground connection: screw type terminals, connection capacity: 1 x 4 mm <sup>2</sup> AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm <sup>2</sup> AWG 11
Marking	CE
Fixing mode	By 4 screws diameter: 7 mm on vertical panel, operating position: horizontal By 4 screws diameter: 7 mm on vertical panel, operating position: vertical By 4 screws diameter: 7 mm on horizontal panel with derating to 90 %

Operating altitude	3000 m
Electrical insulation class	Class B
Width	174.0 mm
Height	169.0 mm
Depth	163.0 mm
Net weight	20.0 kg

## Environment

Product certifications	UR EAC DNV-GL
Standards	UL 506
IP degree of protection	IP20
Environmental characteristic	EMC conforming to EN 62041 Safety conforming to EN 61558-1 Safety conforming to EN 61558-2-4
Protective treatment	TC
Ambient air temperature for storage	-40...80 °C
Overvoltage category	Class I conforming to VDE 0106-1
Dielectric strength	2000 V between winding and ground 4000 V between primary and secondary

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	20.8 kg
Package 1 Height	31 cm
Package 1 width	40 cm
Package 1 Length	40 cm
Unit Type of Package 2	P06
Number of Units in Package 2	4
Package 2 Weight	91.7 kg
Package 2 Height	77 cm
Package 2 width	60 cm
Package 2 Length	80 cm

## Offer Sustainability


Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

# Contractual warranty

Warranty

18 months

**Dimensions**



Dimensions in mm


a	b	c	G	J	Ø
174	167	221	135	141	7

Dimensions in in.

a	b	c	G	J	Ø
6.85	6.57	8.70	5.31	5.55	0.27


**Internal Scheme**

---



## Primary Voltage Wiring

---



**Secondary Voltage Wiring**

---

