Product data sheet Characteristics

LV431536

Earth-leakage add-on protection module, ComPact NSX 250, MH type, 200 VAC to 440 VAC, 30 mA to 10 A, 4 poles



Commercial status

To be discontinued on: 30 June 2021

To be end-of-service on: 30 June 2021

(!) To be discontinued

l	V	1	c	u	I	l	

Range of product	ComPact NSX100250
Range	ComPact
Product or component type	Vigi add-on
Device application	Wiring
Range compatibility	ComPact NSX250 circuit breaker EasyPact CVS250 circuit breaker
Poles description	4P
[In] rated current	250 A
Earth-leakage add-on module name	MH
Earth-leakage protection class	Class A
Residual earth-leakage sensitity adjustment type	Adjustable 5 settings
Earth-leakage sensitivity	0.03 A 0.3 A 1 A 3 A 10 A
Residual earth-leakage time delay adjustment type	Adjustable 4 settings
$[\Delta t]$ residual earth-leakage time delay adjustment	0 ms 310 ms 60 ms 150 ms

Complementary

Network type	AC	
Network frequency	50/60 Hz	 e E
[Ue] rated operational voltage	200440 V AC 50/60 Hz conforming to IEC 60947-2	tou
Earth-leakage protection	With	
Maximum breaking time	800 ms	
Overvoltage category	Class II	

Environment

Electrical shock protection class	Class II
Standards	IEC 60947-2

Packing Units

PCE
1
1.281 kg
13.3 cm
14 cm
17.2 cm
S04
12
16.174 kg
30 cm
40 cm
60 cm
P12
48
76.552 kg
80 cm
80 cm
120 cm

Offer Sustainability

REACh Declaration
REACT Declaration
Compliant EU RoHS Declaration
Yes
Yes
China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months	

LV431536 is replaced by:



Circuit breakers LV429493

Earth-leakage VigiPacT add-on protection module, ComPacT NSX 250, 200 VAC to 440 VAC, 30 mA to 30 A, 4 poles

Qty 1