



# EL3602-0010 | EtherCAT Terminal, 2-channel analog input, voltage, $\pm 75$ mV, 24 bit, high-precision



**i Product status:** Regular delivery

The EL3602-0010 analog input terminal handles signals in the range between  $-75...+75$  mV. The voltage is digitized to a resolution of 24 bits, and is transmitted, electrically isolated, to the higher-level automation device. The input channels of the EtherCAT Terminal have differential inputs and possess a common, internal ground potential. The signal state of the EtherCAT Terminal is indicated by light emitting diodes.

## Product information

### Technical Data

Technical data	EL3602-0010
Number of inputs	2 (differential)
Power supply	via the E-bus
Technology	differential input
Signal voltage	$-75...+75$ mV
Oversampling factor	–
Distributed clocks	–
Distributed clock precision	–
Internal resistance	$> 200$ k $\Omega$
Input filter limit frequency	10 kHz

Common-mode voltage UCM	max. 35 V
Resolution	24 bit (incl. sign)
Conversion time	20 ms default setting, 1...400 ms configurable
Input signal bandwidth	–
Measuring error	< ±0.05 % at 25 °C, 50 Hz filter (relative to full scale value)
Electrical isolation	500 V (E-bus/signal voltage)
Current consumption power contacts	–
Current consumption E-bus	typ. 190 mA
Crosstalk attenuation	> 60 dB
Special features	various filter times, limit value monitoring, high precision
Weight	approx. 60 g
Operating/storage temperature	0...+55 °C/-25...+85 °C
Relative humidity	95 %, no condensation
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
Protect. rating/installation pos.	IP20/variable
Approvals/markings	CE, UL, ATEX
Ex marking	II 3 G Ex nA IIC T4 Gc

<b>Housing data</b>	<b>EL-12-8pin</b>
Design form	compact terminal housing with signal LEDs
Material	polycarbonate
Dimensions (W x H x D)	12 mm x 100 mm x 68 mm
Installation	on 35 mm DIN rail, conforming to EN 60715 with lock
Side by side mounting by means of	double slot and key connection
Marking	labeling of the BZxxx series
Wiring	solid conductor (e), flexible conductor (f) and ferrule (a): spring actuation by screwdriver
Connection cross-section	s*: 0.08...2.5 mm <sup>2</sup> , st*: 0.08...2.5 mm <sup>2</sup> , f*: 0.14...1.5 mm <sup>2</sup>
Connection cross-section AWG	s*: AWG 28...14, st*: AWG 28...14, f*: AWG 26...16
Stripping length	8...9 mm
Current load power contacts	I <sub>max</sub> : 10 A

\*s: solid wire; st: stranded wire; f: with ferrule