



EL3702-0015 | EtherCAT Terminal, 2-channel analog input, voltage, ± 150 mV, 16 bit, oversampling



i Product status: Regular delivery

The EL3702-0015 analog input terminal handles signals in the range between -150 and $+150$ mV and is thus ideally suited for the measurement of shunts and Rogowski coils with built-in integrator. The voltage is digitized to a resolution of 16 bits, and is transmitted, electrically isolated, to the controller. The signals are oversampled with an adjustable, integer multiple (oversampling factor: n) of the bus cycle time (n microcycles per bus cycle). For each microcycle, the EtherCAT Terminal generates a process data block that is transferred collectively during the next bus cycle. The time base of the terminal can be synchronized precisely with other EtherCAT devices via distributed clocks. This procedure enables the temporal resolution of the analog input signals to be increased to n times the bus cycle time. In conjunction with the EL47xx (analog output terminal with oversampling), responses with equidistant time intervals, e.g. in the event of a threshold value being exceeded, become possible. The distributed clocks function enables several EL3702-0015 devices to be synchronized in almost any configuration. The maximum sampling rate per channel is 100 ksamples/s (100,000 samples/s).

Product information

Technical Data

Technical data	EL3702-0015
Number of inputs	2 (differential)
Power supply	via the E-bus
Technology	differential input, oversampling
Signal type	differential
Signal voltage	$-150 \dots +150$ mV

Max. sampling rate	max. 10 µs/100 ksps (per channel, simultaneously)
Oversampling factor	n = 1...100 selectable (max. 100 ksamples/s)
Input signal bandwidth	0...30 kHz recommended
Distributed clocks	yes
Distributed clock precision	<< 1 µs
Internal resistance	> 200 kΩ
Input filter limit frequency	80 kHz
Common-mode voltage UCM	max. 35 V
Conversion time	~ 10 µs per sample
Resolution	16 bit (incl. sign)
Measuring error	< ±0.3 % up to 10 Hz (relative to full scale value)
Electrical isolation	500 V (E-bus/signal voltage)
Current consumption power contacts	–
Current consumption E-bus	typ. 200 mA
Bit width in the process image	input: n x 2 x 16 bit data; optionally 2 x 16 bit cycle counter, 4 byte StartNextLatch time
Special features	oversampling
Weight	approx. 60 g
Operating/storage temperature	0...+55 °C/-25...+85 °C
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protect. rating/installation pos.	IP20/variable
Approvals/markings	CE

Housing data	EL-12-8pin	ES-12-8pin
Design form	compact terminal housing with signal LEDs	terminal housing with pluggable wiring level
Material	polycarbonate	
Dimensions (W x H x D)	12 mm x 100 mm x 68 mm	
Installation	on 35 mm DIN rail, conforming to EN 60715 with lock	
Side by side mounting by means of	double slot and key connection	
Marking	labeling of the BZxxx series	
Wiring	solid conductor (e), flexible conductor (f) and ferrule (a): spring actuation by screwdriver	
Connection cross-section	s*: 0.08...2.5 mm ² , st*: 0.08...2.5 mm ² , f*: 0.14...1.5 mm ²	s*: 0.08...1.5 mm ² , st*: 0.08...1.5 mm ² , f*: 0.14...1.5 mm ²
Connection cross-section AWG	s*: AWG 28...14, st*: AWG 28...14, f*: AWG 26...16	s*: AWG 28...16, st*: AWG 28...16, f*: AWG 26...16

Stripping length	8...9 mm	9...10 mm
Current load power contacts	I _{max} : 10 A	

*s: solid wire; st: stranded wire; f: with ferrule