



# EL4132 | EtherCAT Terminal, 2-channel analog output, voltage, $\pm 10$ V, 16 bit



**i Product status:** Regular delivery

The EL4132 analog output terminal generates signals in the range between -10 and +10 V. The voltage is supplied to the process level with a resolution of 16 bits and is electrically isolated. The output channels of the EtherCAT Terminal have a common ground potential. The EL4132 combines two channels in one housing. The signal state of the EtherCAT Terminal is indicated by light emitting diodes.

## Product information

### Technical data

Technical data	EL4132, ES4132
Connection technology	2-wire, single-ended
Number of outputs	2
Power supply	via the E-bus
Signal voltage	-10...+10 V
Distributed clocks	yes
Distributed clock precision	$\ll 1 \mu\text{s}$
Load	$> 5 \text{ k}\Omega$ (short-circuit proof)
Measuring error	$< 0.1 \%$ (relative to full scale value)
Resolution	16 bit (incl. sign)
Electrical isolation	500 V (E-bus/signal voltage)

Output rate	max. 15 ksps
Current consumption power contacts	–
Current consumption E-bus	typ. 210 mA
Bit width in the process image	2 x 16 bit AO output
Special features	Watchdog parameterizable; user synchronization can be activated.
Weight	approx. 55 g
Operating/storage temperature	-25...+60 °C/-40...+85 °C
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
Protect. rating/installation pos.	IP20/variable
Pluggable wiring	for all ESxxx terminals
Approvals/markings	CE, UL, ATEX
Ex marking	II 3 G Ex nA IIC T4 Gc

Housing data	EL-12-8pin	ES-12-8pin
Design form	compact terminal housing with signal LEDs	terminal housing with pluggable wiring level
Material	polycarbonate	
Dimensions (W x H x D)	12 mm x 100 mm x 68 mm	
Installation	on 35 mm DIN rail, conforming to EN 60715 with lock	
Side by side mounting by means of	double slot and key connection	
Marking	labeling of the BZxxx series	
Wiring	solid conductor (e), flexible conductor (f) and ferrule (a): spring actuation by screwdriver	
Connection cross-section	s*: 0.08...2.5 mm <sup>2</sup> , st*: 0.08...2.5 mm <sup>2</sup> , f*: 0.14...1.5 mm <sup>2</sup>	s*: 0.08...1.5 mm <sup>2</sup> , st*: 0.08...1.5 mm <sup>2</sup> , f*: 0.14...1.5 mm <sup>2</sup>
Connection cross-section AWG	s*: AWG 28...14, st*: AWG 28...14, f*: AWG 26...16	s*: AWG 28...16, st*: AWG 28...16, f*: AWG 26...16
Stripping length	8...9 mm	9...10 mm
Current load power contacts	I <sub>max</sub> : 10 A	

\*s: solid wire; st: stranded wire; f: with ferrule

## Ordering information

Ordering information	
EL4132	EtherCAT Terminal, 2-channel analog output, voltage, ±10 V, 16 bit
ES4132	EtherCAT Terminal, 2-channel analog output, voltage, ±10 V, 16 bit, pluggable wiring