## **Digital InfraRed Video Thermometer**

2.2" Color TFT LCD and Built-in 640 x 480 Camera With a microSD card for capturing images (JPEG) and video (3GP) for viewing on your PC

## **Features:**

- Dual laser indicates ideal measuring distance where the two laser points converge to a 1" target spot
- Fast 150 millisecond response time
- · Color LED bargraph for viewing trends
- Type K Thermocouple input
- Air Temperature and Relative Humidity measurement
- Adjustable emissivity increases measurement accuracy for different surfaces
- Adjustable High/Low set points with audible alarm alerts user when temperature exceeds the programmed set points
- MAX/MIN/AVG/DIF functions
- Trigger lock function for continuous readings
- USB interface
- Auto power off
- Double molded housing
- Complete with microSD card, general purpose Type K bead wire probe, USB cable, rechargeable 3.7V battery, and carrying case





Large 2.2" color video LCD displays measurement area with temperature/humidity, min/max/avg, date,



Upload images and videos to a PC or laptop for further analysis or

Specifications		
Laser Convergence Distance	50" (127cm)	
IR Temperature Range	-58 to 3992°F (-50 to 2200°C)	
Repeatability	±0.5% or 1.8°F/1°C	
Basic Accuracy	$\pm$ (1% of rdg + 4°F/2°C) (31 to 212°F)	
Max resolution	0.1°F/°C	
Emissivity	0.10 to 1.00 Adjustable	
Field of View (Distance to Target)	50:1	
Type K Temperature Range	-58 to 2498°F (-50 to 1370°C)	
Air Temperature Range	32 to 122°F (0 to 50°C)	
Relative Humidity	0 to 100%RH	
LCD Display	2.2" TFT 320 x 240 pixels	
Camera	640 x 480 pixels	
Dimensions	7.4x6.0x2.2" (189x152x57mm)	
Weight	17.4oz (494g)	

## **Ordering Information:**

VIR50Dual Laser Video IR Thermometer\$49		\$499.99
BATT-37VRe	echargeable 3.7V battery	\$39.99

