Before Using the Products

3. Motor Check of the Model





Model Designation



Motor structure

MSMF(Below □80)									
Symbol		Shaft		Holding brake		Oil seal		Motor I/F	
10 dig	11 dig	Round	Key way Threaded	Without	With	Without	With	Connector type	Leadwire type
Α	1								
Α	2								
В	1							•	
В	2								
С	1	•					٠	•	
С	2								
D	1	•						•	
D	2				•		•		
S	1							•	
S	2		٠	•					
Т	1		•					•	
Т	2								
U	1		•						
U	2		•	•					•
V	1								
V	2		•		•		٠		•
						•		•	

Note 🔅 Related page 🔅

• For details of specific model, refer to the Dimensions of Supplement.

• P.1-19 "Check of the Combination of the Driver and the Motor" • P.7-84 to 7-107 "Dimensions of motor"

3. Motor

Check of the Model

Contents of Name Plate

Motor structure

MQMF、MHMF(Below □80)

Symbol		Shaft		Holding brake		Oil seal			Motor I/F	
10	11	D	Key way	Without	\\/:+b		\\/:+b	With	Connector	Leadwire
dig	dig	Rouna	Threaded	without	with	without	with	(Protective lip)	type	type
Α	1									
Α	2									
В	1									
В	2									
С	1									
С	2									
С	3									
С	4									
D	1									
D	2									
D	3									
D	4									
S	1									
S	2									
Т	1									
Η	2									
U	1									
U	2									
U	3									
U	4									
V	1									
V	2									
V	3									
V	4									

MSMF、 MDMF、 MGMF、 MHMF(Above □100)

Symbol		Shaft		Holding brake		Oi	il seal	Motor I/F		
10 dig	11 dig	Round	Key way Threaded	Without	With	With	With (Protective lip)	Connector JN2	Connector JL10	
С	5							•		
С	6								•	
С	7							•		
С	8								•	
D	5							•		
D	6					•			•	
D	7							•		
D	8								•	
G	5							•		
G	6								•	
G	7			•				•		
G	8								•	
Н	5		•		•			•		
Н	6		•			•			•	
Н	7				•			•		
Н	8								•	



• For details of specific model, refer to the Dimensions of Supplement.

Related page • P.1-19 "Check of the Combination of the Driver and the Motor" • P.7-84 to 7-107 "Dimensions of motor"

5

Setup

7