Product data sheet Characteristics

TSXSAY1000C

coated AS-Interface master module - V2 - standard and extended

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 2,656.50 USD



NИ	\sim	ın

Main		- 4
Range of product	Modicon Premium Automation platform	- 5
Product or component type	AS-Interface master module	_ :

Complementary

Range compatibility	AS-Interface cabling system
Actuator sensor interface profile [AS-i]	M2E
AS-i version	V2
Addressing	Standard and extended
Number of slave	31, extended 31, standard
Type of connectable interfaces	Analog I/Os, standard Discrete I/Os (4I/3O), extended Discrete I/Os (4I/4O), standard Safety interfaces, standard
Electrical connection	1 male connector SUB-D, 3 ways
Supply	Via power supply integrated into the host platform of the module
Current consumption	450 mA 5 V DC
Local signalling	Display unit
Number of modules per base controller	1 TSX570. 1 TSX57C. 2 TSX571. 4 TSX572. 8 TSX573. 8 TSX574. 8 TSX575. 8 TSX576.
Protective treatment	Conformal coating Humiseal 1A33
Net Weight	0.75 lb(US) (0.34 kg)

Environment

LITVITOTITICITE		2
Standards	IEC 60068-2-27, Ea tests IEC 60068-2-6, Fc tests	This
Ambient air temperature for operation	32140 °F (060 °C)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient air temperature for storage	-13158 °F (-2570 °C)
IP degree of protection	IP20

Ordering and shipping details

Packing Units

Package 1 Height	2.17 in (55.000 mm)
Package 1 width	7.09 in (180.000 mm)
Package 1 Length	10.24 in (260.000 mm)

Contractual warranty

Warranty	18 months