

NEW

High Accuracy & Performance Digital Multimeter

TY700 series Advanced Type TY720/Standard Type TY710

Most Reliable Handheld DMM

•Highest Precision

- Basic accuracy 0.020%
- True RMS measurement

•New Functions for Electronic and Industrial Use

- Simultaneous measurement and display of DC and AC
- Switchable RMS/MEAN detection*
- Low-pass Filter (LPF)*
- AC50mV range*
- Lo-Power resistance measurement*

*TY720 only

•Full Support for Data Management

- A large-capacity logging-mode memory
- TY720: 10,000 data
- TY710: 1,000 data
- USB communication, application software (Optional DMM communication package)

•Safe Design and Wide Temperature Range for Harsh Use

- Conforms to safety standards EN61010-1 1000V CAT. III, 600V CAT. IV
- Safety shutters for preventing erroneous insertion of test leads into current measurement terminals
- Operating temperature range -20 to +55°C
- Storage temperature range -40 to +70°C

•Closed Case Calibration

•3-year Warranty



Advanced type
TY720

Standard type
TY710

Model and Specification Code		Optional Accessories		
Name	Model	Name	Model	Specification
Digital Multimeter	TY710	DMM communication package	92015	USB communication adapter + USB communication cable + Application software
	TY720	Communication package for printer	97016	Printer adapter + Printer cable
		Printer	97010	Thermal printer Paper width 112mm
		AC adapter for printer	94005	AC 100V ± 10%
			94006	For Printer, Europe
		Thermal printing paper	97080	10 rolls (1 set)
		Test leads	98015	1000V CAT III , 600V CAT IV Red/black (1 set)

TY700 General Specifications

Measurement Functions	:DC voltage, AC voltage, DCV+ACV, DC current, AC current, DCA+ACA, resistance, frequency, temperature, capacitance, duty cycle, decibel calculation, continuity check, diode test, low-power resistance (TY720 only)
For AC voltage/current, RMS/Mean detection can be switched (TY720 only).	
For AC voltage/current, the low-pass filter can be turned on/off (TY720 only).	
Additional Functions	:Data hold/auto hold/peak hold (TY720 only), range hold, maximum/minimum/average values resistance, capacitance zero, relative and percentage value calculation, manual-mode memory, logging-mode memory, auto power off, backlight (white LED)
Display	:5-digit LCD: 7-segment Digital display: Main display; [50,000] counts Sub-display; [50,000] counts Bar graph display: 51-segment Polarity indicator: "+" appears automatically when the polarity is negative Overrange indicator: "OL" Low-battery indicator: "+" appears at or below the minimum operating voltage.

Performance

Test conditions: Temperature and humidity = 23 ± 5°C, 80% RH or less; Accuracy = ± (% rdg + dg). Note: A response time is the time required for achieving the accuracy specified for the corresponding range.

DC Voltage Measurement (:-V)

Range	Resolution	Accuracy		Input Resistance	Maximum Input Voltage
		TY710	TY720		
50mV	0.001mV	0.05±10			
500mV	0.01mV	0.02±2		Approx. 100MΩ	1000V DC
2400mV	0.1mV				
5V	0.0001V	0.025±5			
50V	0.001V				
500V	0.01V	0.03±2			
1000V	0.1V			10MΩ	1000V rms AC

NMRR: 80dB or greater for 50/60Hz ± 0.1% At 50mV of range, 70dB or greater for 50/60Hz ± 0.1%

CMRR: 100dB or greater for 50/60Hz(Rs=1kΩ) Response time: 0.3 seconds or less

AC Voltage Measurement [RMS] (-V)

Range	Resolution	Accuracy (Upper: TY710; Lower: TY720; the display of "—" is not specified)						Input Impedance	Maximum Input Voltage
		10 - 20Hz	20 - 1kHz	10kHz	10k - 20kHz	20k - 50kHz	50k - 100kHz		
50mV	0.001mV	2+80 ²	0.4+40 ²	5+40 ²	5.5+40 ²	—	15+40 ²	11MΩ<50pF	1000V rms AC
500mV	0.01mV	—	—	—	—	—	—		
5V	0.0001V	1.5+30 ¹	0.7+30 ¹	2+50 ²	1+40 ¹	2+70 ²	5+200 ²		
50V	0.001V	1+30 ¹	0.4+30 ¹	—	—	—	—		
500V	0.01V	—	—	—	—	—	—		
1000V	0.1V	— ²	— ²	3+30 ²	— ²	— ²	— ²	10MΩ<50pF	1000V DC

*1: At 5 to 100% of range

*2: At 10 to 100% of range CMRR: 80dB or greater for DC to 60Hz(Rs=1kΩ) Response time: 1 second or less

AC Voltage Measurement [MEAN] (-V)

Range	Resolution	Accuracy						Input Impedance	Maximum Input Voltage
		10 - 20Hz	20 - 500Hz	500 - 1kHz	—	—	—		
50mV	0.001mV	4+80 ²	1.5+30 ²	5+30 ²	—	—	—	11MΩ<50pF	1000V rms AC
500mV	0.01mV	—	—	—	—	—	—		
5V	0.0001V	2+30 ¹	—	1+30 ¹	—	—	—		
50V	0.001V	—	—	—	—	—	—		
500V	0.01V	—	—	—	—	—	—		
1000V	0.1V	— ²	— ²	— ²	— ²	— ²	— ²	10MΩ<50pF	1000V DC

*1: At 5 to 100% of range

*2: At 10 to 100% of range CMRR: 80dB or greater for DC to 60Hz(Rs=1kΩ) Response time: 1 second or less

DCV + ACV (:-V)

Range	Resolution	Accuracy (Upper: TY710; Lower: TY720; the display of "—" is not specified)						Input Impedance	Maximum Input Voltage
		DC, 10 - 20Hz	DC, 20Hz - 1kHz	DC, 1k - 10kHz	DC, 10k - 20kHz	DC, 20k - 50kHz	DC, 50k - 100kHz		
5V	0.0001V	1.5+10 ¹	1+10 ¹	2+10 ²	—	—	—	11MΩ<50pF	1000V rms AC
50V	0.001V	1.5+10 ¹	0.5+10 ¹	1+10 ¹	2+10 ²	5+20 ²	—		
500V	0.01V	—	—	—	—	—	—		
1000V	0.1V	— ²	— ²	— ²	— ²	— ²	— ²		

*1: At 5 to 100% of range

*2: At 10 to 100% of range CMRR: 80dB or greater for DC to 60Hz(Rs=1kΩ) Response time: Approx. 2 seconds

Resistance Measurement (Ω)

Range	Resolution	Accuracy		Maximum Testing Current	Open-circuit Voltage	Input Protection Voltage
		TY710	TY720			
500Ω	0.01Ω	—	—	<1mA	—	—
5kΩ	0.0001kΩ	0.1+2 ¹	0.05+2 ¹	<0.25mA	—	—
50kΩ	0.001kΩ	—	—	<25μA	—	—
500kΩ	0.01kΩ	—	—	<2.5μA	—	—
5MΩ	0.0001MΩ	—	—	<1.5μA	—	—
50MΩ	0.01MΩ	1+2	—	<0.13μA	—	—

*1: Accuracy after zero calibration Response time: 1 second or less for 500Ω to 50kΩ, 5 seconds or less for 5MΩ to 50MΩ

Low-power Resistance Measurement (LP-Ω)

Range	Resolution	Accuracy		Maximum Testing Current	Open-circuit Voltage	Input Protection Voltage
		TY720	—			
5kΩ	0.001kΩ	—	—	<10μA	—	—
50kΩ	0.01kΩ	0.2+3	—	<1.0μA	—	—
500kΩ	0.1kΩ	—	—	<0.6μA	—	—
5MΩ	0.001MΩ	1+3	—	<0.05μA	—	—

*1: Accuracy after zero calibration

*2: At 40 to 100% of input voltage or current range

Continuity Check (Ω)

Maximum effective display: 5000 Range: Resolution: Continuity Beeper TY710, TY720 Testing Current: Open-circuit Voltage: Input Protection Voltage:

500Ω 0.1Ω Buzzer sounds at 100 ± 50Ω or less.

Approx. 0.5mA <5V 1000V rms

Subject to change without notice.

All Rights Reserved. Copyright © 2008, Yokogawa Meters & Instruments Corporation.

Measuring Rate : 6 times/sec (Frequency: 1 time/sec, Capacitance: max. 0.03 times/sec (50mF), Resistance: 4 times/sec)

Operating Temp. and Humidity : -20 to 55°C, 80% RH or less (no condensation) 40 to 55°C: 70% RH or less

Storage Temp. and Humidity : -40 to 70°C, 70% RH or less (no condensation)

Temperature Coefficient : Add the accuracy 0.05/°C to the basic accuracy at a temperature within -20 to 18°C and 28 to 55°C.

Power Supply : Four AA (R6) dry cells

Battery Life : Approx. 120 hours (for continuous DC voltage measurement with alkaline cells)

Withstanding Voltage : 6.88kV for 5 seconds (between input terminals and casing)

Dimensions : Approx. 90(W x 192(H) x 49(D) mm

Weight : Approx. 560g (including batteries)

Compliance with Standards : Safety EN61010-1, EN61010-031, 1000V CAT III, 600V CAT IV, pollution level 2, indoor, 2000m max. above sea level EMC: EN61326-1 Class B, EN55011 Class B Group 1

Standard Accessories : AA (R6) dry cells: 4, Test lead set (98015): 1, Fuse (installed) 440mA/1000V and 10A/1000V, Instruction manual: 1

DC Current Measurement (:-A)

Range	Resolution	Accuracy			Voltage Drop	Maximum Input Current
		TY710	TY720	TY710, TY720; the display of "—" is not specified		
500µA	0.01µA	—	—	—	<0.11mV/µA	440mA
5000µA	0.1µA	—	—	—	<4mV/mA	fuse-protected
50mA	0.001mA	—	—	—	—	—
500mA ^a	0.01mA	—	—	—	—	—
5A	0.0001A	—	—	—	—	10A
10A	0.001A	—	—	—	—	10A

Response time: 0.3 seconds or less *3: Maximum testing current at 500mA of range is 440mA

Shown above is the accuracy at 5 to 100% of range (10 to 100% for 10A range). Response time: 1 second or less

*3: Maximum testing current at 500mA of range is 440mA.

AC Current Measurement [RMS] (-A)

||
||
||